



Tesmec TRS 1300 Super

Excavating in hard ground for large diameter services? Our Tesmec TRS 1300 Super is the perfect solution. With cutting chains varying from 700mm to 950mm in width, our 600hp trencher can excavate trenches to suit service installation up to 700mm diameter. We provide an experienced operator, support truck and mechanic to ensure maximum production on your site.

Trenching Specifications

Trench cutting chain widths	700mm and 950mm
Cutting teeth	150 Teeth
Trenching productivities (1.5m deep trench)	50-1000m/day with an average of 325m/day
Rock / soil strengths	100MPa-1MPa
Typical daily servicing and maintenance time for fair wear and tear	2-3 hours/day
Average G.E.T. (Ground Engaging Tool - Teeth) usage	10/Day

Plant Specifications

Length	14.4m
Width	3.35m
Height	3.9m
Weight	75 tonnes
Engine	CAT C16 ACERT - 600hp

Fuel Usage

Average	45 Litres/Hour
High	90 Litres/Hour

For rates, equipment availability or more information call

Nathan LeBrun
M: 0418 603 765
nathan.lebrun@dmcivil.com.au

Scott Feilding
M: 0439 921 626
scott.feilding@dmcivil.com.au

GUARANTEED PERFORMANCE

T: (08) 9492 1800
dmc@dmcivil.com.au